



## CN5614RV - V.92 56Kbps Internal Data/Fax/TAM Modem

CN5614RV is an internal software modem. It comes with complete Voice Mail and Telephone Answering capabilities that allow the modem to receive and take messages from incoming voice calls. The V.92 technology saves your time and money with nearly twice faster than the download speed of V.34 modems. The Plug-&-Play function simplifies your installation in a few minutes.

### KEY FEATURES

- Connect Faster: Quick Connect Reduces up to 50% of Start-up/Connect Time
- Upload Faster: 48Kbps Maximum Upload Speed Reduces the Time for Files Transmission
- Modem-on-Hold Feature Allows Users to Receive an Incoming Call and Stay Connected to the Internet
- Provide Data/Fax/TAM Communication Software

### PRODUCT SPECIFICATIONS

Model	CN5614RV
Data Mode	<ul style="list-style-type: none"> <li>• ITU-T V.92 Data Modem with receive rates up to 56k bps and send rates up to 48 kbps</li> <li>• ITU-T V.90 Data Modem with receive rates up to 56k bps and send rates up to V.34 rates.</li> <li>• ITU-T V.34, V.32 bis, V.32, V.22 bis, V.22, V.23, and V.21, Bell 212A and Bell 103</li> <li>• ITU-T V.42 LAPM and MNP 2-4 Error Correction</li> <li>• ITU-T V.44, V.42 bis and MNP 5 Data Compression</li> </ul>
Fax Mode	<ul style="list-style-type: none"> <li>• Fax Modem with send and receive rates Up to 14.4 kbps</li> <li>• ITU-T V.17, V.29, V.27 ter, and V.21 channel 2</li> <li>• EIA/TIA 578 Class 1 and T.31 class 1.0 command sets</li> </ul>
TAM Mode	<ul style="list-style-type: none"> <li>• TAM: V.253 commands</li> <li>• Sampling Rate Voice 7.2KHz using 2,3 or 4 bits ADPCM, 11.025 KHz linear PCM</li> <li>• ITU-T V.80</li> </ul>
Interface	<ul style="list-style-type: none"> <li>• Two RJ-11 jacks for line &amp; phone connection</li> <li>• PCI Rev 2.2 compliant interface for host computer</li> </ul>
System Requirement	<ul style="list-style-type: none"> <li>• Pentium 166 MHz MMX-compatible PC or Greater.</li> <li>• 32 Mbytes RAM or more.</li> <li>• 50 Mbytes Free Disk Space or More.</li> </ul>
Environment	<ul style="list-style-type: none"> <li>• Operating Temperature: -20° ~ 70°C (-4° ~ 158°F)</li> <li>• Storage Temperature: -40° ~ 80°C (-40° ~ 176°F)</li> <li>• Humidity: 10% ~ 90% Non-condensing</li> </ul>
Certifications	<ul style="list-style-type: none"> <li>• CE, FCC</li> </ul>
Dimensions (L x W)	<ul style="list-style-type: none"> <li>• 120 x 42 mm (4.72 x 1.65 inches)</li> </ul>
Software Support	<ul style="list-style-type: none"> <li>• MS Windows 98SE/ME/2000/XP</li> </ul>

### ORDERING INFORMATION

Model	Description
CN5614RV	V.92 56Kbps Internal Data/Fax/TAM Modem