



ORDERING INFORMATION

Model	Description
CN5614XE	V.92 56Kbps External Data/Fax/Voice Modem

CN5614XE - V.92 56Kbps External Data/Fax/Voice Modem

CN5614XE is an external voice, fax, and data modem. This model allows users to speak hand free over the phone line via its Full-duplex Audio system. It comes with complete Voice Mail and Telephone Answering capabilities that allow the modem to receive and take messages from incoming voice calls. CN5614XE is fully compliant with current Windows 95 and Windows 98 standards. The modem package contains an external modem, RJ-11 phone cable, quick installation guide, CD-Title with drivers, communication software, AC adapter and an RS-232 cable.

KEY FEATURES

- Connect Faster: Quick Connect Reduces Start-up/Connect Time by up to 50%
- Upload Faster: 48Kbps Maximum Upload Speed Reduces the Time to Send Files, Emails, Graphics and Video
- Modem-on-Hold Feature Allows You to Receive an Incoming Call and Stay Connected to the Internet
- Provide Data/Fax/Voice Communication Software

PRODUCT SPECIFICATIONS

Model	CN5614XE
Data Mode	<ul style="list-style-type: none"> • ITU-T V.92 Data Modem with receive rates up to 56k bps and send rates up to 48 kbps • ITU-T V.90 Data Modem with receive rates up to 56k bps and send rates up to V.34 rates • ITU-T V.34, V.32 bis, V.32, V.22 bis, V.22, V.23, and V.21, Bell 212A and Bell 103 • ITU-T V.42 LAPM and MNP 2-4 Error Correction • ITU-T V.44, V.42 bis and MNP 5 Data Compression
Fax Mode	<ul style="list-style-type: none"> • Fax Modem with send and receive rates Up to 14.4 kbps • ITU-T V.17, V.29, V.27 ter, and V.21 channel 2 • EIA/TIA 578 Class 1 commands
Voice Mode	<ul style="list-style-type: none"> • TAM: V.253 commands • Speakerphone: 1. Full-duplex, echo-cancelled digital speakerphone 2. ITU-T V.70 DSVD upgrade option
Interface	<ul style="list-style-type: none"> • Two RJ-11 jacks for line & phone connection • Two audio jacks for speaker & microphone connection • One RS-232 jack for host computer connection
System Requirement	<ul style="list-style-type: none"> • Pentium 166 MHz MMX-compatible PC or Greater. • 32 Mbytes RAM or more. • 50 Mbytes Free Disk Space or More.
Power	<ul style="list-style-type: none"> • External AC 9V, 1A
Environment	<ul style="list-style-type: none"> • Operating Temperature: -20° ~ 70°C (-4° ~ 158°F) • Storage Temperature: -40° ~ 80°C (-40° ~ 176°F) • Humidity: 10% ~ 90% Non-condensing
Certifications	<ul style="list-style-type: none"> • CE, FCC
Dimensions (L x W x H)	<ul style="list-style-type: none"> • 170 x 125 x 34.5mm (6.69x 4.92 x 1.35inches)
Software Support	<ul style="list-style-type: none"> • MS Windows 98SE/ME/2000/XP