



## ORDERING INFORMATION

Model	Description
CNAD800-RF (B)	ADSL PCI Modem

## CNAD800-RF –ADSL PCI Modem

CNet CNAD800-RF connects your Windows computer to standard ADSL service to provide a high-speed "always on" connection to the Internet. The CNAD800-RF is compatible with all major operating systems by using an available PCI interface. Just simply plug into any phone jack with ADSL service and run the software wizard and you can be ready for instant Internet connection.

### Key Features

- Simple Plug-&-Play Installation
- Compatible for all major ADSL Standards
- Reach in Distance up to 18,000 Feet
- Simple and Intuitive Graphical User Interface

## SPECIFICATIONS

Model	CNAD800-RF
ADSL Data Mode	<ul style="list-style-type: none"> <li>• G.992.1 (G.DMT): Downstream and Upstream data rates up to 8Mbps and 1Mbps</li> <li>• G.992.2 (G.Lite): Downstream and Upstream data rates up to 1.5Mbps and 512Kbps</li> </ul>
ATM Protocol	<ul style="list-style-type: none"> <li>• WAN Mode Support: PPP Over ATM (RFC2364) and PPP Over Ethernet (RFC2516)</li> <li>• LAN Mode Support: Routed/Bridge Ethernet Over ATM (RFC1483)</li> <li>• Classical Internet Protocol Over ATM (RFC1577)</li> </ul>
System Requirement	<ul style="list-style-type: none"> <li>• Pentium II compatible processor and above</li> <li>• 64MB RAM or more</li> <li>• 50MB of free disk space for driver installation</li> <li>• CD-ROM drive</li> </ul>
Interface	<ul style="list-style-type: none"> <li>• Compliant with PCI Local Bus Specification, Revision 2.2</li> <li>• Compliant with PCI Bus Power Management Interface Specification, version 1.1 or 1.0</li> </ul>
Environment	<ul style="list-style-type: none"> <li>• Operating Temperature: -20° ~ 70°C (-4° ~ 158°F)</li> <li>• Storage Temperature: -40° ~ 80°C (-40° ~ 176°F)</li> <li>• Humidity: 10% ~ 90% Non-condensing</li> </ul>
Certifications	<ul style="list-style-type: none"> <li>• CE, FCC</li> </ul>
Dimensions (L x W)	<ul style="list-style-type: none"> <li>• 154 x 92 mm (6.06 x 3.62inches)</li> </ul>
Software Support	<ul style="list-style-type: none"> <li>• MS Windows 98SE/ME/2000/XP</li> </ul>