

CSH-2402 – 24-Port 10/100Mbps Fast Ethernet Switch with 2 port share Copper/Fiber

Just attach your network cables to either of these Switches, and you will instantly add 24 brand new bandwidths to your network. The switches let users divide their networks into 24 independent network segments. A major advantage is each port provides its own bandwidth. This makes shifting available bandwidths as easy as changing a cable. Each port is further equipped with a built-in Auto-negotiation function that senses for the fastest possible speed (10Mbps to 200Mbps), then automatically sets the port to operate at that speed. The dual speed capability makes the switch the perfect bridge for connecting 100Mbps with 10Mbps segments.

KEY FEATURES

- 24 10/100Mbps Switch Ports with 2 ports share Copper/Fiber by push button
- Each Port Creates an Independent Network Segment
- Support Store-and-Forward Technology
- Support IEEE 802.3x Flow-control for Full-duplex and Back Pressure Flow Control for Half-duplex
- Bridging Capability for 100Mbps and 10Mbps Segments
- All Ports Support Auto-MDI/MDI-X and Auto-negotiation Functions

PRODUCT SPECIFICATIONS

Model	CSH-2402
Standards	<ul style="list-style-type: none"> · IEEE 802.3: 10BASE-T · IEEE 802.3u: 100BASE-TX · IEEE 802.3x: Flow-control for Full-duplex operation
Ports	· 24 Ports 10BASE-T /100BASE-TX with 2 ports share Copper/Fiber (100BASE-FX)
Media Support	<ul style="list-style-type: none"> · 10BASE-T: Category 3, 4 or 5 TP · 100BASE-TX: Category 5 TP · 100BASE-FX: 62.5/125um Multi-mode fiber cable(SC type connector)
Bandwidth	<ul style="list-style-type: none"> · 10BASE-T: 10/20Mbps · 100BASE-TX: 100/200Mbps · 100BASE-FX: 100/200Mbps
Forwarding/Filtering Rate	<ul style="list-style-type: none"> · 14881 packets/second per port @ 10Mbps, maximum · 148810 packets/second per port @ 100Mbps, maximum
Duplex Modes	· Support Auto-negotiation and Auto-MDI/MDI-X functions
Switch	<ul style="list-style-type: none"> · When SW1 OFF,SW2 OFF ; port 12,24 are TP ports · When SW1 OFF,SW2 ON ; port 12 is Fiber port, port 24 is TP port · When SW1 ON,SW2 OFF ; port 12 is disable, port 24 is TP port · When SW1 ON,SW2 ON ; port 12,24 are Fiber ports
LED Indicators	<ul style="list-style-type: none"> · One LED displays Power status · One LED per port displays Link/ACT status
Power Supply	<ul style="list-style-type: none"> · Internal Full Range Auto-Switching · Input voltage: 100 ~ 240 +/-10% VAC/ 50 ~ 60 Hz
Power Consumption	· 13.2 watt maximum
Environment	<ul style="list-style-type: none"> · Operating Temperature: 0° ~ 45°C (32° ~ 113°F) · Storage Temperature: -20° ~ 70°C (-4° ~ 158°F) · Humidity: 10% ~ 90% Non-condensing
Certifications	· CE,FCC
Dimensions (L x W x H)	· 442 x 130 x 44mm(17.40 x 5.12 x 1.73 inches)